

TAM-212

Satellite Terminal

The battery-powered TAM-212 satellite terminal from Honeywell Global Tracking allows tracking and monitoring of fixed and mobile assets such as trailers, containers, tanks and railcars, even in the most remote and hostile places in the world.

Once an asset has been equipped with a TAM-212 and deployed in the field, the terminal automatically selects the most appropriate satellite and regularly transmits its location and any additional message data via secure systems.

This slimline solution requires no external power source as an internal battery will provide up to five years of maintenance-free operation.

Like many of Honeywell Global Tracking's terminals, the TAM-212 uses the Inmarsat constellation of satellites and the IsatM2M standard. This connectivity method delivers an affordable and reliable direct-to-desktop information service with fast and easy-to-use message handling.

In addition to using fixed mounting points, the TAM-212 incorporates strong magnetic feet, making it possible for users to quickly install and de-install the device without damaging any asset surfaces.



Features

- **Global Coverage:** Offers secure satellite connectivity worldwide
- **Always Connected:** Tracks and monitors mobile assets at any time, anywhere in the world
- **Long-lasting Battery:** Offers up to five years of maintenance-free operation
- **Affordable and Reliable:** Field-proven and cost-effective tracking solution for a wide range of applications
- **Flexible Mapping:** Facilitates viewing of assets using Google and Bing maps in a standard browser, or integrates data feeds into custom enterprise resource planning (ERP) solutions
- **Multiple I/O Ports:** Connected external sensors can report additional data, e.g., speed, tire pressure and fuel consumption; ideal for fleet management applications
- **Optional Alert Button:** Convenient in-vehicle button allows drivers to immediately warn others of dangers

TAM-212 Technical Specifications

Physical	
Dimensions	247 mm x 178 mm x 48 mm (9.7" x 7.0" x 1.9")
Weight	1.5 kg (3.3 lbs)
Mounting	Screws, magnetic feet
Environmental	
Operating Temperature	-35°C to +55°C (-31°F to +131°F)
Humidity	≤95% @ +40°C (+104°F) non-condensing
IP Rating	IP66
Interfaces	
Serial Interface	Asynchronous serial RS232
Baud Rate	9600 bps
Parity/Data Bits/Stop Bits	N, 8, 1
Satellite Connectivity	
Transmitter	EIRP: 0-9dBW Modulation 2 level FSK: 20 Hz tone spacing Tx burst duration: 2s or 8s
Receiver	G/T: ≥-25dB/K at EL = 30° Modulation: 32-ary FSK, 20Hz tone spacing
Elevation Angle	0° - 90°
Frequency Range	Transmit: 1626.5-1660.5 MHz Receive: 1525.0-1559.0 MHz GPS: 1575.42 ± 1.0 MHz
GPS	Channels: 50 Typical time to first fix: Cold Start: <29 seconds Hot Start <1s (GPS was off for less than 2 hours) Typical position accuracy: (SA Off): 2.5m (CEP, 2D) Dynamic capability: Velocity 515 m/s maximum Acceleration ≤4g Maximum update rate 1s

For more information:

www.gt.honeywell.com

Honeywell Global Tracking

Miller Court, Severn Drive
Tewkesbury, Gloucestershire
GL20 8DN UK
www.honeywell.com

TAM-212 DS Rev A 12/11
© 2011 Honeywell International Inc.

